

PLAYGRASS 24 COLOR

APPLICATION ANWENDUNG / APPLICATION / TOEPASSING APLICACIÓN / APPLICAZIONE	MULTI-SPORT
PRODUCTION METHOD HERSTELLUNGSVERFAHREN / MODE DE FABRICATION / PRODUCTIEPROCES PROCESO DE FABRICACIÓN / PROCESSI DI FABBRICAZIONE	TUFTED
FIBRE FASER / FIBRE / VEZEL FIBRA / FIBRA	PE 8.800 DTEX
COLOUR FARBE / COULEUR / KLEUR / COLOR / COLORE	ANTHRACITE/BLUE/BROWN/RED/ORANGE/GREY YELLOW/GREEN/OLIVE/TERRA/WHITE/BLACK
PILE HEIGHT POLHÖHE / HAUTEUR DU VELOURS / POOLHOOGTE ALTURA DE LA PILA / ALTEZZO FELPA	± 24 MM
TOTAL HEIGHT GESAMTHÖHE / HAUTEUR TOTALE / TOTALE HOOGTE ALTURA TOTAL / ALTEZZO TOTALE	± 26 MM
PILE WEIGHT POLEINSATZGEWICHT / POIDS DU VELOURS / POOLGEWICHT PESO DE LA PILA / PESO FELPA	± 1.100 GR/M2
TOTAL WEIGHT GESAMTGEWICHT / POIDS TOTAL / TOTAALGEWICHT PESO TOTAL / PESO TOTALE	± 2.240 GR/M2
GAUGE TUFTTEILUNG / JAUGE / TUFTDELING / GALGA / SCARTAMENTO	3/8"
STITCHES (10 CM1) STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL PUNTADAS / SERRAGGIO PUNTI	± 20
STITCHES (M2) STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL PUNTADAS / SERRAGGIO PUNTI	± 21.000
PRIMARY BACKING TRÄGER / DOSSIER PRIMAIRE / TUFTDOEK BACKING PRINCIPAL / SUPPORTO PRIMARIO	PP ± 190 GR/M2
SECONDARY BACKING RÜCKEN / DOSSIER SECONDAIRE / SECUNDAIRE BACKING BACKING SECUNDARIO / SUPPORTO SECONDARIO	LATEX ± 950 GR/M2
WATER PERMEABILITY WASSERDURCHLASSIGKEIT / PERMÉABILITÉ / WATERDOORLATENDHEID PERMEABILIDAD AL AGUA / PERMEABILITÀ ACQUA	± 60 L/MIN/M2
UV-STABILITY UV-STABILITÄT / STABILITÉ UV / UV STABILITEIT ESTABILIDAD UV / STABILITÀ UV	DIN 53387
ROLL WIDTH ROLLBREITE / LARGEUR DES ROULEAUX / ROLBREEDTE ANCHO DE ROLLO / LARGHEZZA ROTOLO	2,00 M / 4,00 M
ROLL LENGTH ROLLÄNGE / LONGUEUR DES ROULEAUX / ROLLENGTE LARGO DEL ROLLO / LUNGHEZZA ROTOLO	± 30 M



All data are subject to typing errors and modifications based on technical improvements or company-internal developments. Europe Grass reserves the right to alter technical specifications due to variations in raw materials and production circumstances. All figures are average values and can vary slightly from different production runs. Only use rolls of the same batch.

Safefloor ApS
 Bjødstrupvej 10
 8410 Rønne
 Denmark

+45 86 15 19 25
 info@safefloor.dk
 www.safefloor.dk